

Supreme Heat Rejection-Pro

Designed to reduce up to 46% Solar heat & Give up to 73% VLT

Supreme Heat Rejection-Pro Film, also known as "IR FILM" is a high performance window film, which offers consumers the high-end performance properties without usage of metalized film in product design.

Disclaimer: All values as applied to 1/8 inch Clear Plate Glass. Tests are representative of actual production & may vary from batch to batch.

	SHR Pro Black 60	SHR Pro Black 70	SHR Pro Greenish Grey 70	SHR Pro Greenish Grey 75
Thickness	2 Mil	2 Mil	2 Mil	2 Mil
Visible Light Transmittance	62%	71%	68%	73%
Visible Light Tolerance	62 ± 3.0	71 ± 3.0	68 ± 3.0	73 ± 3.0
Visible Light Reflectance	8%	8%	9%	9%
Solar Energy Transmittance	42%	50%	39%	44%
Solar Energy Reflectance	7%	7%	8%	8%
Solar Energy Absorbance	51%	43%	53%	48%
Ultra Violet Transmittance	< 1%	< 1%	< 1%	< 1%
Shading Coefficient	0.65	0.71	0.62	0.66
Glare Reduction	32%	22%	25%	20%
Total Solar Energy Rejection	44%	38%	46%	43%
NIR Blocking at 1025 nm	68 ± 3.0	58 ± 3.0	80 ± 3.0	70 ± 3.0